













ACCESSORIES | LAMP OPTIONS

| LAMP | COMMENTS | WATTAGE | BEAM ANGLE | FOR USE WITH |
|---|------------------------|---------|-------------|--|
|  Xenolux MR-8 | 8000 Average Life Hour | 20 | Wide | CG |
| | | 20N | Narrow | CG |
|  Halogen MR-8 | 4000 Average Life Hour | 20 | Wide | CG |
|  Xenolux MR-11 | 8000 Average Life Hour | 20 | Wide | MP |
| | | 20N | Narrow | MP |
|  Halogen MR-11 | 4000 Average Life Hour | 20 | Wide | MP |
|  Xenolux MR-16 | 8000 Average Life Hour | 10 | Wide | LO, LR, MU, RS, TE |
| | | 20 | Wide | LO, LR, MU, RS, TE |
| | | 20N | Narrow | LO, LR, MU, RS, TE |
| | | 35N | Narrow | LO, LR, MU, RS, TE |
| | | 50 | Wide | LO, LR, MU, TE |
| | | 50VW | Very Wide | LO, LR, MU, TE |
|  Halogen MR-16 | 4000 Average Life Hour | 20 | Wide | LO, LR, MU, RS, TE |
| | | 20V | Very Narrow | LO, LR, MU, RS, TE |
| | | 35 | Wide | LO, LR, MU, RS, TE |
| | | 35V | Very Narrow | LO, LR, MU, RS, TE |
| | | 50N | Narrow | LO, LR, MU, TE |
| | | 50V | Very Narrow | LO, LR, MU, TE |
|  Xenolux T3 | 8000 Average Life Hour | 10 | N/A | BD, CA, CB, CM, CP, CR, CV, DL, DM, DP, DR, DS, EA, GT, LM, MM, PF, PR, PV, QF, RL, SC, SP |
| | | 20 | N/A | BD, CA, CB, CM, CR, CV, DL, DM, DP, DR, DS, EA, GT, PF, PR, PV, QF, RL, SC, SP |
| | | 35 | N/A | CM, CR, DR, DS, GN, RL |
|  Halogen T3 | 2000 Average Life Hour | 20 | N/A | SI |
|  Halogen AR-11 | 2000 Average Life Hour | 20 | Wide | CL, ML, PM, TC, TS, VL |
| | | 35 | Wide | CL, TC, TS |
|  Halogen AR-20 | 2000 Average Life Hour | 50N | Narrow | TS |
|  Incandescent 93 | 900 Average Life Hour | 12 | N/A | AL, FG, LS, TD |
|  Incandescent 1141 | 1200 Average Life Hour | 18 | N/A | AL, FG, TD |

Beam Angle Key (approximate values)
 Very Narrow- 10°
 Narrow- 25°
 Wide- 40°
 Very Wide- 60°